

Configuration

- The Basics
 - Example
- Dynamic configuration with the ConfigResolver
 - Scope
 - ConfigResolver Usage
 - Inject the ConfigResolver in your services
- Custom locale configuration

The Basics

Important

Configuration is tightly related to the service container.

To fully understand the following content, you need to be familiar with [Symfony's service container](#) and [its configuration](#).

Basic configuration handling in eZ Platform is similar to what is commonly possible with Symfony. Regarding this, you can define key/value pairs in [your configuration files](#), under the main **parameters** key (like in **parameters.yml**).

Internally and by convention, keys follow a **dot syntax** where the different segments follow your configuration hierarchy. Keys are usually prefixed by a *namespace* corresponding to your application. Values can be anything, **including arrays and deep hashes**.

eZ Platform core configuration is prefixed by **ezsettings** namespace, while *internal* configuration (not to be used directly) is prefixed by **ezpublish** namespace.

For configuration that is meant to be exposed to an end-user (or end-developer), it's usually a good idea to also [implement semantic configuration](#).

Note that it is also possible to [implement SiteAccess aware semantic configuration](#).

Example

Configuration

```
parameters:  
    myapp.parameter.name: someValue  
    myapp.boolean.param: true  
    myapp.some.hash:  
        foo: bar  
        an_array: [apple, banana, pear]
```

Usage from a controller

```
// Inside a controller  
$myParameter = $this->container->getParameter( 'myapp.parameter.name' );
```

Dynamic configuration with the ConfigResolver

In eZ Platform it is fairly common to have different settings depending on the current siteaccess (e.g. languages, [view provider configuration](#)).

Scope

Dynamic configuration can be resolved depending on a **scope**.

Available scopes are (in order of precedence) :

1. *global*
2. SiteAccess
3. SiteAccess group
4. *default*

It gives the opportunity to define settings for a given siteaccess, for instance, like in the [legacy INI override system](#).

This mechanism is not limited to eZ Platform internal settings (aka **ezsettings namespace**) and is applicable for specific needs (bundle-related, project-related, etc.).

Always prefer semantic configuration especially for internal eZ settings.

Manually editing internal eZ settings is possible, but at your own risk, as unexpected behavior can occur.

ConfigResolver Usage

Dynamic configuration is handled by a **config resolver**. It consists in a service object mainly exposing `hasParameter()` and `getParameter()` methods. The idea is to check the different *scopes* available for a given *namespace* to find the appropriate parameter.

In order to work with the config resolver, your dynamic settings must comply internally with the following name format: `<namespace>. <scope>. parameter.name`.

The following configuration is [an example of internal usage](#) inside the code of eZ Platform.

Namespace + scope example

```
parameters:  
    # Some internal configuration  
    ezsettings.default.content.default_ttl: 60  
    ezsettings.ezdemo_site.content.default_ttl: 3600  
  
    # Here "myapp" is the namespace, followed by the siteaccess name as the parameter  
    # scope  
    # Parameter "foo" will have a different value in ezdemo_site and ezdemo_site_admin  
    myapp.ezdemo_site.foo: bar  
    myapp.ezdemo_site_admin.foo: another value  
    # Defining a default value, for other siteaccesses  
    myapp.default.foo: Default value  
  
    # Defining a global setting, used for all siteaccesses  
    #myapp.global.some.setting: This is a global value
```

```

// Inside a controller, assuming siteaccess being "ezdemo_site"
/** @var $configResolver \eZ\Publish\Core\MVC\ConfigResolverInterface **/
$configResolver = $this->getConfigResolver();

// ezsettings is the default namespace, so no need to specify it
// The following will resolve ezsettings.<siteaccessName>.content.default_ttl
// In the case of ezdemo_site, will return 3600.
// Otherwise it will return the value for ezsettings.default.content.default_ttl (60)
$locationViewSetting = $configResolver->getParameter( 'content.default_ttl' );

$fooSetting = $configResolver->getParameter( 'foo', 'myapp' );
// $fooSetting's value will be 'bar'

// Force scope
$fooSettingAdmin = $configResolver->getParameter( 'foo', 'myapp', 'ezdemo_site_admin' );
// $fooSetting's value will be 'another value'

// Note that the same applies for hasParameter()

```

Both `getParameter()` and `hasParameter()` can take 3 different arguments:

1. `$paramName` (i.e. the name of the parameter you need)
2. `$namespace` (i.e. your application namespace, `myapp` in the previous example. If null, the default namespace will be used, which is **ezsettings** by default)
3. `$scope` (i.e. a siteaccess name. If null, the current siteaccess will be used)

Inject the ConfigResolver in your services

Instead of injecting the whole ConfigResolver service, you may directly inject your SiteAccess-aware settings (aka dynamic settings) into your own services.

You can use the **ConfigResolver** in your own services whenever needed. To do this, just inject the `ezpublish.config.resolver` service:

```

parameters:
    my_service.class: My\Cool\Service

services:
    my_service:
        class: %my_service.class%
        arguments: [@ezpublish.config.resolver]

```

```

<?php
namespace My\Cool;

use eZ\Publish\Core\MVC\ConfigResolverInterface;

class Service
{
    /**
     * @var \eZ\Publish\Core\MVC\ConfigResolverInterface
     */
    private $configResolver;

    public function __construct( ConfigResolverInterface $configResolver )
    {
        $this->configResolver = $configResolver;
        $myParam = $this->configResolver->getParameter( 'foo', 'myapp' );
    }

    // ...
}

```

Custom locale configuration

If you need to use a custom locale they can also be configurable in `ezplatform.yml`, adding them to the *conversion map*:

```

ezpublish:
    # Locale conversion map between eZ Publish format (i.e. fre-FR) to
    # POSIX (i.e. fr_FR).
    # The key is the eZ Publish locale. Check locale.yml in
    EzPublishCoreBundle to see natively supported locales.
    locale_conversion:
        eng-DE: en_DE

```

A locale *conversion map* example can be found in the `core` bundle, on `locale.yml`.

- Content Repository configuration
- Dynamic settings injection
- Logging & Debug configuration
- Persistence cache configuration
- Session cookie configuration
- View provider configuration