

ez_trans_prop

- Description
- Prototype and Arguments
 - Main language use
- Usage

Description

`ez_trans_prop()` is a generic, low level Twig helper which corrects the translated value of a multi valued(translations) property.

If the current language cannot be found as a translation for content, the main language (see [further down for details](#)) will be used if this is supported by the provided **object**. This behavior is identical when forcing a language using **forcedLanguage**.

Prototype and Arguments

`ez_trans_prop(ValueObject object, string property[, string forcedLanguage])`

Argument name	Type	Description
object	eZ\Publish\Core\Repository\Values\ValueObject	ValueObject object property belongs to.
property	string	Property to get translated value from, logic is using one of the following (<i>in this order</i>): <ul style="list-style-type: none">▪ <i>object method</i> "get{property}"▪ <i>object property</i> "{propertys}"
forcedLanguage	string	Optional language we want to force (<i>e.g. "eng-US"</i>), otherwise takes prioritized languages from SiteAccess settings.

Main language use

Main language is attempted to be applied in the following way for Value objects that support this:

- *When attribute is retrieved via object property:* Use **mainLanguageCode** property if it exists as fallback language, but only if either **alwaysAvailable** property does not exists or is true.
- *When attribute is retrieved via object method:* Provide `$language = null` as the only argument to the method, depends on logic of ValueObject if this gives a fallback value or not

Usage

Example below shows how this function can be used to get the Content name with exact same result as using `ez_content_name(content)`

```
{{ ez_trans_prop( versionInfo, "name" ) }}
```

Example for ContentType->names:

```
{{ ez_trans_prop( contentType, "name" ) }}
```