

# Legacy configuration injection

For better integration between 5.x (symfony based) kernel and legacy (4.x) kernel, injection is used to inject settings, `session` and current siteaccess from 5.x into legacy using an event: `kernel.event_subscriber`

- Injected settings
  - Database settings
  - Storage settings
  - Image settings
  - Using ImageMagick filters
  - Extending injected settings
  - Site settings
- Injected Behavior
  - eZFormToken (CSRF) integration
  - ezpEvent (Cache clear) integration

## Injected settings

Several settings are injected to avoid having to duplicate settings across new and old kernel, this is done in `eZ\Bundle\EzPublishLegacyBundle\LegacyMapper\Configuration`.

For mappings below, yml settings prefixed with `ezpublish` are system settings, while the rest are settings you can define per siteaccess.

### For versions 5.1, 5.2 and 5.3

When viewing `ini` settings in the Administration Interface, settings for other siteaccess may be incorrectly displayed if the configuration has been modified in Symfony configuration.

## Database settings

The settings for "Server", "Port", "User", "Password", "Database" and "DatabaseImplementation" are set based on the current settings in your yml files, either from the explicit settings defined below, or the "dsn"

**Mapping:**

yml	site.ini [DatabaseSettings]
server	Server
port	Port
user	User
password	Password
database_name	Database
type	DatabaseImplementation

## Storage settings

The settings for "VarDir" and "StorageDir" are set based on current settings in your yml files as shown below.

**Mapping:**

yml	site.ini [FileSettings]
var_dir	VarDir
storage_dir	StorageDir

## Image settings

Some of the settings for image sub system are set based on your yml files as shown below.

### Mapping:

yml	image.ini
ezpublish.image.temporary_dir	[FileSettings]\TemporaryDir
ezpublish.image.published_images_dir	[FileSettings]\Published\Images
ezpublish.image.versioned_images_dir	[FileSettings]\Versioned\Images
image_variations	[FileSettings]\AliasList
ezpublish.image.imagemagick.enabled	[ImageMagick]\IsEnabled
ezpublish.image.imagemagick.executable_path	[ImageMagick]\ExecutablePath
ezpublish.image.imagemagick.executable	[ImageMagick]\Executable
imagemagick.pre_parameters	[ImageMagick]\PreParameters
imagemagick.post_parameters	[ImageMagick]\PostParameters
ezpublish.image.imagemagick.filters	[ImageMagick]\Filters

#### Image aliases : image\_variations

Note : for image\_variations the *small* value is referenced in ezo configuration and this configuration needs to be changed if the small variation is removed.

## Using ImageMagick filters

The following block shows a valid ImageMagick filter usage example for `ezpublish.yml`:

### ImageMagick filters usage example

```
ezpublish:  
    imagemagick:  
        filters:  
            geometry/scale: "-geometry {1}x{2}"
```

Since ImageMagick filter usage changed from eZ Publish 4.x versions you can find the list of filters existing by default to use eZ Publish 5.x:

### ImageMagick filters list for yml

```
sharpen: "-sharpen 0.5"  
  
geometry/scale: "-geometry {1}x{2}"  
  
geometry/scalewidth: "-geometry {1}"  
  
geometry/scaleheight: "-geometry x{1}"  
  
geometry/scaledownonly: "-geometry {1}x{2}>"  
  
geometry/scalewidthdownonly: "-geometry {1}>"  
  
geometry/scaleheightdownonly: "-geometry x{1}>"
```

geometry/scaleexact: "-geometry {1}x{2}!"
geometry/scalepercent: "-geometry {1}x{2}"
geometry/crop: "-crop {1}x{2}+{3}+{4}"
filter/noise: "-noise {1}"
filter/swirl: "-swirl {1}"
colorspace/gray: "-colorspace GRAY"
colorspace/transparent: "-colorspace Transparent"
colorspace: "-colorspace {1}"
border: "-border {1}x{2}"
border/color: "-bordercolor rgb({1},{2},{3})"
border/width: "-borderwidth {1}"
flatten: "-flatten"
resize: "-resize {1}"

For more details on setting ImageMagick filters on image.ini please refer to the [\[imagemagick\] / filters](#) documentation.

## Extending injected settings

It's possible to add your own kernel event subscriber and also inject your own settings by following how it is done in LegacyMapper\Configuration, and then at the end merge it with existing injected settings, like so:

<b>injected-settings</b>
\$event->getParameters()->set(     "injected-settings",     \$settings + (array)\$event->getParameters()->get( "injected-settings" ) );

## Site settings

You can inject the site.ini SiteAccessSettings in your ezpublish.yml file.

yml	site.ini[SiteAccessSettings]
location_id	PathPrefix
excluded_uri_prefixes	PathPrefixExclude
	[SiteSettings]
location_id	IndexPage
	DefaultPage
	RootNode

**ezpublish.yml**

» [Expand](#)

[source](#)

```
ezpublish:
    system:
        ezdemo_site_group:
            content:
                tree_root:
                    # Root locationId. Default is top locationId
                    location_id: 123
                    # Every URL aliases starting with those prefixes will be
considered
                    # being outside of the subtree starting at root_location.
                    # Default value is an empty array.
                    # Prefixes are not case sensitive.
                    excluded_uri_prefixes: [ /media, /images ]
```

## Injected Behavior

In addition to injected settings, some injection of behavior is also performed.

### eZFormToken (CSRF) integration

This feature is only available as of eZ Publish 5.1 (2013.01)

If your config.yml setting have `framework.csrf_protection.enabled` set to `true`, then both `kernel.secret` and `framework.csrf_protection.field_name` will be sent to `ezxFormToken` class so csrf protection in legacy uses the same token and form field name.

By making sure all your Symfony forms uses the provided csrf protection, forms with `intention=legacy` can be set up to send data to legacy kernel:

```
$formOptions = array( 'intention' => 'legacy' );
$form = $this->createFormBuilder( null, $formOptions )
    ->...
    ->getForm();
```

`framework.csrf_protection.field_name` shouldn't be changed as that would prevent `eZFormToken` from working with most AJAX custom code

### ezpEvent (Cache clear) integration

A listener is set up for both content/cache and content/cache/all to make sure Symfony (Internal proxy or Varnish with custom vcl) HTTP cache is cleared when cache is cleared in eZ Publish admin interface.